


Filter + Regulator + Lubricator Combinations

5 micron element, 12 bar (174 psig) regulator + gauge and wall mounting bracket



Ordering information


Port size	Flow [‡] scfm	Weight kg (lb)	Combined manual / semi-auto drain Part number [†]	Auto drain Part number [†]
3/4"	170	3.3 (7.3)	P3YCB96SECNFLNF	P3YCB96SEANFLNF
1"	170	3.3 (7.3)	P3YCB98SECNFLNF	P3YCB98SEANFLNF

† Standard part numbers shown in bold. For other models refer to Options chart below.

‡ Flow with 10 bar (145 psig) inlet pressure, 6.3 bar (91.4 psig) set pressure and 1 bar (14.5 psig) pressure drop.

Filter / Regulator + Lubricator Combinations

5 micron element, 12 bar (174 psig) regulator + gauge and wall mounting bracket



Ordering information

Port size	Flow [‡] scfm	Weight kg (lb)	Combined manual / semi-auto drain Part number [†]	Auto drain Part number [†]
3/4"	315	2.8 (6.2)	P3YCA96SECNFLNF	P3YCA96SEANFLNF
1"	340	2.8 (6.2)	P3YCA98SECNFLNF	P3YCA98SEANFLNF

† Standard part numbers shown in bold. For other models refer to Options chart below.

‡ Flow with 10 bar (145 psig) inlet pressure, 6.3 bar (91.4 psig) set pressure and 1 bar (14.5 psig) pressure drop.

Options

P3YCA		9	6	SE	C	N	F	LNF
Basic series		Thread type*		Port size		Drain type		Adjustment range
Filter / Regulator + Lubricator	P3YCA	BSPP	1	3/4	6	C	Combined manual / semi-auto drain	F 0-12 bar (0 to 174 psi) with gauge
Filter + Regulator + Lubricator	P3YCB	NPT	9	1	8			
						A	Auto drain	
							J	0-16 bar (0 to 232 psi) with gauge

* **Note:** For 1-1/2" ported unit, please order P3YKA*BCP port block kit separately.

Bold items are most common.

* Note: For 1-1/2" ported unit, please order P3YKA*BCP port block kit separately.

Bold items are most common.