Rittal – The System.

Faster – better – everywhere.

NH fuse-switch-disconnectors, size 00 to 3 – SV 9343.210

Date : Aug 22, 2022

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

NH fuse-switch-disconnectors, size 00 to 3 – SV 9343.210

created: 22.08.2022 on www.rittal.com/com-en



Product description

Material:	Polyamide Fire protection corresponding to UL 94 Contact tracks: Electrolytic copper, silver-plated
Colour:	Chassis: RAL 7035 Cover: RAL 7035/7001
Basis of test:	IEC/DIN EN 60 947-3 DIN EN 60 269-2 (fuse inserts)
Note:	The technical data may vary for UR applications. Applications to UR only in conjunction with "Special Purpose Fuses".

Product description

Design:	Size: 2
To fit busbars:	with cross-section height: 5 mm with cross-section height: 10 mm
Number of poles:	3-pole
For bar systems with centre-to-centre spacing:	60 mm
Dimensions:	Width: 210 mm Height: 298 mm

Type of electrical connection:	Screw M10
Rated operating voltage:	690 V, 3~
Clamping area for laminated copper bars:	Width: 50 mm Height: 10 mm
Connection for round conductor cross-sections:	10 mm² - 240 mm²
Rated operating current max.:	400 A
Cable outlet:	Top/bottom
Packs of:	1 pc(s).
Weight/pack:	3.36 kg
Copper weight (kg per piece):	1
EAN:	4028177540392
Customs tariff number:	85369095
ETIM 7.0:	EC001040
ETIM 6.0:	EC001040
eCl@ss 8.0/8.1:	27371401
eCl@ss 6.0/6.1:	27371401
Product description:	SV NH fuse-switch disconnector, size 2, 400 A, 690 V, 3-pole, screw M10

Approvals

Approvals:	C-UR CCC UR UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity