


Popular Combinations: Inlet pressure 90 psig (6.2 bar), and 0.3 psig (5 bar) pressure drop.




**Filter/Regulator + Lubricator Combinations, metal bowl, manual twist drain
40 micron element, 125 psig (8.6 bar) regulator without gauge**



Port size	Bowl type	Relief type	Manual twist drain
3/4"	Metal, twist drain	Relieving	P3NCA96SGMNNLNA
1"	Metal, twist drain	Relieving	P3NCA98SGMNNLNA
1-1/2" #	Metal, twist drain	Relieving	P3NCA9PSGMNNLNA



**Filter + Regulator + Lubricator Combinations, metal bowl, manual twist drain
40 micron element, 125 psig (8.6 bar) regulator without gauge**



Port size	Bowl type	Relief type	Manual twist drain
3/4"	Metal, twist drain	Relieving	P3NCB96SGMNNLNA
1"	Metal, twist drain	Relieving	P3NCB98SGMNNLNA
1-1/2" #	Metal, twist drain	Relieving	P3NCB9PSGMNNLNA

Notes: All combo part numbers are with regulator knob in up position.
BSPP ported units supplied using NPT ported bodies and BSPP port block kits.
1" Port body with 1-1/2" port block

Ordering information:

P3N

C

A

9

6

S

G

M

N

N

L

N

A

Type

Combination, modular C

Combination

2-unit, hi-flow, metal bowl A

3-unit, hi-flow, metal bowl B

Port Type

G thread (BSPP) female 1

NPT female 9

Port Size

3/4" (w/o port blocks) 6

1" (w/o port blocks) 8

1-1/2" port blocks (w/ 1" ported body) P

Bowl

Metal bowl w/ sight gauge S

Element

40 micron G

Relief

N Relieving

Drains

M Twist drain

A Auto float drain

Mounting Option

A No bracket or kits

B Wall bracket

Lubricator Drain / Fill Device

N No drain, solid bowl / fill plug

Lubricator Type

L Oil mist w/ polycarbonate sight dome

Pressure Gauge

N 125 psi (0 to 8 bar), without gauge

H 250 psi (0 to 17 bar), without gauge

G 125 psi (0 to 8 bar), with gauge

J 250 psi (0 to 17 bar), with gauge

Note: All configured BSPP ported units are supplied using NPT ported bodies and BSPP port block kits.

Most popular.



For inventory, lead times, and kit lookup, visit www.pdnplu.com